

# SPHERE AMENITY LIGHTING

## A SPHERICAL LUMINAIRE WITH AN EFFECTIVE LIGHT DISTRIBUTION FOR LARGE AREA AMENITY APPLICATIONS.

- Clear polycarbonate sphere with coated upper canopy for effective control of upward light. (Black).
- Aluminium louvre provides a controlled distribution pattern and minimises glare.
- Optional 180° spill shield for effective control of overspill.
- Optics and control gear sealed to IP65.
- Easy access to lamp and gear via removing bowl.
- Integral control gear.
- Factory fitted photocell option.
- Post top mounting (76mm)
- Typical mounting height of 5m to 6m.

## APPLICATIONS

- Shopping precinct.
- Retail parks.
- Car parks.
- Residential.
- Parks & Gardens.

## PRODUCT CODES

CODE	CANOPY COLOUR	LAMP WATTAGE	LAMP TYPE	LAMP	LAMP STYLE	LAMP LUMENS	WEIGHT	WINDAGE
<b>HIGH PRESSURE SODIUM</b>								
ARG 070SLPB	Black	70	SON	E27		6000	6.0kg	0.17m <sup>2</sup>
ARG 150SLPB	Black	150	SON	E40	TUBULAR	17500	6.0kg	0.17m <sup>2</sup>
<b>METAL HALIDE</b>								
ARG 070HLPB	Black	70	MH	E27		5300	6.0kg	0.17m <sup>2</sup>
ARG 150HLPB	Black	150	MH	E40	TUBULAR	14000	6.0kg	0.17m <sup>2</sup>
<b>CERAMIC METAL HALIDE</b>								
ARG 070CHLPB	Black	70	CDO-TT	E27	TUBULAR	6300	6.0kg	0.17m <sup>2</sup>

## CODE ACCESSORIES

PC	Factory fitted Photocell
1414PC	180° Spill Shield for Louvre

